

Multiquip WT5C

The WT5C (surge brakes) & WTE5C (electric brakes) are industrial 525 Gal. Mobile Water Trailers with trusted MQ 2" Centrifugal Pumps

The Multiquip WT5C Water Trailer is ready to tackle a host of assignments to include: Dust Control, Emergency Fire Fighting Response, Construction, Agricultural Support and Equipment Wash Down. This mobile unit features: DOT approved Double-Axle Trailer, trusted high-flow MQ [QP2H](#) Centrifugal Pump, flexible Suction/Discharge manifold system with simple valve operations, and a rugged 525 GAL polyethylene Water Tank. The model WTE5C provides electric brakes.

- Store up to 525 gallons of water in a durable polyethylene water tank with integrated baffles to support water movement during transportation
- Dependable performance with Multiquip [QP2H](#) 2 inch centrifugal pump
- Components protected from damage by low profile manifold assembly
- Switch easily from suction to discharge mode by turning a single manifold lever
- Rear spray bar operates under pressurized or gravity feed settings
- Quickly fill tank through 2" diameter steel pipe with QD coupler or vented 12" diameter fill port
- Rapid hose setup with standard Quick Disconnect (cam & groove) fittings
- Transport hoses and accessories in convenient steel storage bin
- Safe towing and braking assured by a dual axle trailer and rugged hydraulic brake system
- Convenient Hose Kit provided (2" x 20' Suction & 2" x 50' Discharge)



Unit Specifications

Water Tank	525 Gal. Polyethylene
Trailer	DOT certified, dual axle, 3500 LB.
Power Source	HONDA GX120 recoil start
Pump	Multiquip QP2H 2 in. Centrifugal
Flow / Head	158 GPM / 115 Ft.
Manifold	1.5" & 2" Left/Rt. (QD Couplers), three garden hose valves, rear spray bar

Dimensions & Weights

Overall Length	146 in	3708.4 mm
Overall Width	68 in	1727.2 mm
Overall Height	80 in	2032 mm
Shipping Weight	1,428 lb	647.73 kg

Notice: Features and equipment specifications are subject to change without notice.